

# Technical Data Sheet

## STA Brickseal

Construction Chemicals

<b>Description</b>	: Brickseal is a cavity wall bituminous water-proofer
<b>Product Code</b>	: Brickseal
<b>Suitability</b>	: Especially suited for the construction industry
<b>Applications</b>	: Two coats of Brickseal is applied with a block brush to prevent pin holes after the first coat is obliterated : Must be applied to the outer finish of the inner skin of a 230mm wall
<b>Customer Benefits</b>	<ul style="list-style-type: none"> <li>• Specifically designed for creating a waterproof layer between two brick skins</li> <li>• Can be used as a bond breaker between two concrete finishes.</li> <li>• Coverage: +-2-4m<sup>2</sup></li> <li>• Equipment can be cleaned with water immediately after Brickseal use.</li> </ul>

Typical Characteristics	Typical Properties	
	Units	Typical Result
Colour (Visual)	-	Black
Odour (Olfactory)	-	Negligible
Drying time (Observation)	-	2-4hrs
Acidity	-	Neutral to Alkaline

<b>Product Specifications</b>	: meets typical properties stated above					
<b>Packing</b>	<b>500ml</b>	<b>1Lt</b>	<b>5Lt</b>	<b>20Lt</b>	<b>210Lt</b>	<b>1 000Lt</b>
	<b>N</b>	<b>N</b>	<b>Y</b>	<b>Y</b>	<b>Y</b>	<b>N</b>

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.