

Technical Data Sheet

DVO 400

Mould & Shutter Release Oil

Description	: DVO 400 is a specially formulated ready-to-use Mould and Shutter Release Oil which can be applied directly onto the moulds by brush, rag, roller or conventional mould oil
Product Code	: DVO 400
Suitability	: Especially suited for construction applications
Applications	: This product should be applied in one continuous film. Concreting: Concrete may be poured immediately after application. Recoat moulds and formwork if concreting is scheduled or delayed more than 2-days after initial coat. Post Mould Release: Clean formwork as soon as possible to remove excess dust. Should be re-applied immediately to protect steel moulds from rust. On used moulds, all traces of adherent material, either concrete or previous oil deposits, must be removed prior to use.
Customer Benefits	<ul style="list-style-type: none"> Minimizes the amount of cleaning required prior to the re-use of the formwork. On new moulds no preparation is necessary. Limited deterioration of coverage for up to 3 months High coverage rate - ±30m² per litre No significant staining or discolouration. Excellent mould release with a smooth surface finish Suitable for all year-round use Tested and proven in the harsh South African environment.

Typical Characteristics	Typical Properties	
	Units	Typical Result
Colour	-	Brown to Red
Odour	-	Negligible
API Density @ 20°C	kg/l	0.8580
Viscosity @ 40°C	cSt	15
Flash Point COC	°C	100 Min
Pour Point	°C	-5 Max

Product Specifications	: meets typical requirements of DVO 400					
Packing	1L	5Lt	20Lt	25Lt	210Lt	1 000Lt
	N	Y	Y	Y	Y	Y

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.