

# Technical Data Sheet

## LF50 Mould Oil

neat general-purpose mould & shutter release oil

<b>Description</b>	: LF50 is a neat general-purpose mould & shutter release oil
<b>Product Code</b>	: LF50
<b>Suitability</b>	: Especially suited for industrial applications
<b>Applications</b>	: Apply by means of a spray, sponge, cloth or mop leaving a thin film on the mould or shuttering surface.
<b>Customer Benefits</b>	<ul style="list-style-type: none"> <li>• High coverage rate - <math>\pm 30\text{m}^2</math> per litre</li> <li>• No significant staining or discolouration.</li> <li>• Excellent mould release with a smooth surface finish.</li> <li>• Suitable for all year-round use.</li> <li>• Tested and proven in the harsh South African environment.</li> </ul>

Typical Characteristics	Typical Properties	
	Units	Typical Result
Colour	-	Light Golden Brown to Red
Odour	-	Negligible
API Density @ 15°C	kg/l	0.83
Viscosity @ 40°C	cSt	5-15
Flash Point COC	°C	100 Min
Pour Point	°C	-5 Max

<b>Product Specifications</b>	: meets typical requirements of LF50 Mould oil					
<b>Packing</b>	<b>500ml</b>	<b>1Lt</b>	<b>5Lt</b>	<b>20Lt</b>	<b>210Lt</b>	<b>1 000Lt</b>
	<b>N</b>	<b>N</b>	<b>Y</b>	<b>Y</b>	<b>Y</b>	<b>Y</b>

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.