

# Technical Data Sheet

## LP 50/50

Emulsifiable concrete mould releasing agent

|                          |   |
|--------------------------|---|
| <b>Description</b>       | : LP 50/50 is an emulsifiable concrete mould releasing agent.   |
| <b>Suitability</b>       | : Suitable for all year-round use   |
| <b>Application</b>       | : Dilute at a ratio of 1part concentrate up to 4 parts water, being the maximum practical mix.<br>: whilst stirring add water ratio to the oil to form the emulsion.<br>: Trial dilutions recommended.<br>: Apply by means of a spray, sponge, cloth or mop leaving a thin film on the mould or shuttering surface.                                   |
| <b>Customer Benefits</b> | <ul style="list-style-type: none"> <li>• Limited deterioration of coverage.</li> <li>• High coverage rate</li> <li>• No significant staining or discolouration</li> <li>• Excellent mould release with a smooth surface finish.</li> <li>• Tested and proven in the harsh South African environment.</li> </ul>                                       |
| <b>Storage</b>           | : Product is to be stored in a cool, dry, stable temperature (non-heat fluctuating) environment, out of direct sun and UV Light to prevent quality loss.<br>: Product should be kept away from direct natural elements and oxidizing agents.<br>: All drummed concentrate should be stored indoors and protected from heat, humidity, light and dust. |

| Typical Characteristics | Typical Properties |                           |
|-------------------------|--------------------|---------------------------|
|                         | Units              | Typical Result            |
| Appearance              | -                  | Light golden brown to Red |
| Odour                   | -                  | Typical                   |
| Density @ 15°C          | Kg/l               | 0.86                      |
| Viscosity @ 40°C        | cSt                | 32                        |
| Flash Point (COC)       | °C                 | 180 min                   |
| Pour Point              | °C                 | -5 max                    |

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.

# Technical Data Sheet

## LP 50/50

Emulsifiable concrete mould releasing agent

|                |              |            |            |             |              |                |
|----------------|--------------|------------|------------|-------------|--------------|----------------|
| <b>Packing</b> | <b>500ml</b> | <b>1Lt</b> | <b>5Lt</b> | <b>25Lt</b> | <b>210Lt</b> | <b>1 000Lt</b> |
|                | <b>N</b>     | <b>N</b>   | <b>N</b>   | <b>Y</b>    | <b>Y</b>     | <b>N</b>       |

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.