

Technical Data Sheet

Plastermate

Emulsion Bonding Agent

Description	: Plastermate is an emulsion-bonding agent, containing a plasticised vinyl homopolymer emulsion.
Suitability	: Suitable for all year-round use
Application	: Formulated to provide a solution to bond plaster to any surface that must be plastered.
Customer Benefits	<ul style="list-style-type: none"> • Prevents chipping, hacking or slashing of surfaces. • It bonds new concrete to old. • It can even be used in the plastering of glass, tiles and the like, with amazing results to any building surfaces. • Coverage: +/- 50 sqm. /5lt.
Storage	<p>: Product is to be stored in a cool, dry, stable temperature (non-heat fluctuating) environment, out of direct sun and UV Light to prevent quality loss.</p> <p>: Product should be kept away from direct natural elements and oxidizing agents.</p> <p>: All drummed concentrate should be stored indoors and protected from heat, humidity, light and dust.</p>

Typical Characteristics	Typical Properties	
	Units	Typical Result
Appearance	-	White emulsion
Solid Content	-	17.6%
pH		5.5
Viscosity @ 25°C	cPs	740-760cPs

Packing	500ml	1Lt	5Lt	25Lt	210Lt	1 000Lt
	N	N	Y	Y	N	N

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.