

Technical Data Sheet

SCP Mould Oil

Neat spun concrete pipe mould oil

Description	: SCP Mould Oil is a neat spun concrete pipe mould oil
Suitability	: Suitable for all year-round use
Application	: Apply by means of a spray, sponge, cloth, or mop by leaving a thin film on the mould or shuttering surface.
Customer Benefits	<ul style="list-style-type: none"> • High coverage rate: +/- 30m² per litre • No significant staining or discolouration • Excellent mould release with a smooth surface finish. • Tested and proven in the harsh South African environment.
Storage	<p>: Product is to be stored in a cool, dry, stable temperature (non-heat fluctuating) environment, out of direct sun and UV Light to prevent quality loss.</p> <p>: Product should be kept away from direct natural elements and oxidizing agents.</p> <p>: All drummed concentrate should be stored indoors and protected from heat, humidity, light and dust.</p>

Typical Characteristics	Typical Properties	
	Units	Typical Result
Appearance	-	Brown to Red
Odour	-	Typical
Density @ 15°C	Kg/l	0.83
Viscosity @ 40°C	cSt	5-10
Flash Point (COC)	°C	70 min
Pour Point	°C	-5 max

Packing	500ml	1Lt	5Lt	20Lt	210Lt	1 000Lt
	N	N	Y	Y	Y	Y

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.