

Technical Data Sheet

WPD 58

Neat waxy oil-based wood pallet preserver

Description	: WPD 58 is a neat waxy oil-based mould, shutter, and coffer release oil.
Suitability	: Suitable for all year-round use
Application	: Apply by means of a spray, sponge, cloth, or mop by leaving a thin film on the mould or shuttering surface.
Customer Benefits	<ul style="list-style-type: none"> • High coverage rate: +/- 30m² per litre • Limited deterioration of coverage for up to 6 months. • Hard wearing and can give up to 3 releases per coating. • Preserves wood and steel moulds and shutters from natural elements. • Tested and proven in the harsh South African environment.
Storage	<p>: Product is to be stored in a cool, dry, stable temperature (non-heat fluctuating) environment, out of direct sun and UV Light to prevent quality loss.</p> <p>: Product should be kept away from direct natural elements and oxidizing agents.</p> <p>: All drummed concentrate should be stored indoors and protected from heat, humidity, light and dust.</p>

Typical Characteristics	Typical Properties	
	Units	Typical Result
Appearance	-	Light golden brown
Odour	-	Typical
Density @ 15°C	Kg/l	0.875
Viscosity @ 40°C	cSt	60-80
Flash Point (COC)	°C	100 min
Pour Point	°C	15 min
Wax Content	% wt	18-24

Packing	500ml	1Lt	5Lt	25Lt	210Lt	1 000Lt
	N	N	N	Y	Y	N

Information in this TDS is from available published sources and internal analysis and is believed to be accurate. No warrant, express or implied, is made and Stacor (Pty) LTD assumes no responsibility resulting from the in-correct use of this TDS. The user must determine suitability of this information for his/her application.